

CV0204DVR



CV0204DVR	
Functionality	Simplex
Video Compression	Modified MJPEG
Resolution	720 x 480
Recording Frame Rate	Max 120 FPS, 30FPS per camera channel
Recording Time	Max 120 Days, 30 Days w/ 4 Cameras
Recording Resolution	Max 640 x 224
Recording Qualities	Low, Medium, High
Recording Modes	Manual, Schedule, Motion Detection
Recording Method	Quad, Each
Recording Media	3.5" 160GB IDE HDD
Storage Capacity	Max. 750GB Hard Drive
Video Format	NTSC
Video Loss	Auto Detection
Video Inputs	4CH BNC
Video Display Output	1CH BNC
Live Viewing	Quad View, Single Screen
Live Resolution	720 x 480
Live Frame Rate	Max 120 FPS
Play Search Mode	By Time, Date, Event
Play Speed	Normal, Fast Forward
Play Mode	Quad, Each
OSD and System Menu Display	Yes
OSD Language Display	English/Traditional Chinese
Time and Date Stamp Display	Yes
Password Protection	Menu Password, Stop Recording Password
Network Protocol	TCP/IP, PPPoE, DDNS, SMPT
Network LAN IP	Static, Dynamic

Network Connection	10/100 BaseT Ethernet (RJ-45)
Operating System	Written Using Linux
Processor	Proprietary
Disk Full Warning	Yes
Automatic Overwrite Option	Yes
LED Indicators	Power, Record, Play, Live
Housing Material	Aluminum
Housing Color	Graphite Grey
Power Input	DC 12V 2A
Power Adapter Input	AC 100-250V 50/60Hz
Operating Temperature	41°F ~ 104°F
Operating Humidity	30% ~ 80%
Dimensions	12.6" x 1.8" x 10.6"
Weight	6.6lbs (without HDD)

CAMERA (CV67)	
Camera Type	Bullet
Image Sensor	1/4" CCD Color
Resolution	420 TV Lines
Outdoor Use	Yes
IP Rating	IP65
Focal Length	3.6mm
Focus Type	Fixed
Night Vision	Yes
Number of IR LEDs and Range	15, up to 10ft
IR LED Control	Automatic, CDS Sensor
Min. Illumination	0 lux
IR Wavelength	850nm
Video Output	4 PIN DIN to RCA w/ 60ft Extension Wire
TV System	NTSC
Microphone	No
Motion Detection	No
Viewing Angle	60 Degrees
Electronic Shutter	1/50 ~ 1/500000 sec
BLC	No
AGC	Auto

ELC	Auto
Line Lock	No
Iris Control	No
White Balance	Auto
Sun Shield	Yes
IR Cut Filter	No
Housing Material	Anodized Aluminum
Housing Color	Platinum Silver
Signal/Noise Ratio	>48dB
Camera Bracket	Yes
Operating Temperature	-14°F ~ 122°F
Operating Humidity	98%
Camera Power Input	DC 12V 200mA
Power Adapter Input	120V 60Hz
LED Power Indicator	No
Dimensions	5.3" x 4.5" x 2.3"
Weight	0.8lbs (with stand)